

YOUTH

ATV125-05

125cc Entry-Level ATV

An entry-level ATV for specialist off-road dealers. Rider suitability must follow the model manual.



Reference configuration | Off-road applications

Engine	125cc Single-cylinder, 4-stroke, Air-cooled, Fully Automatic Transmission, Electric Start
Drive System	Chain Drive
Ignition System	CDI
Frame	Heavy-duty Steel Frame
Handlebar	Steel Handlebar with Hand Guards
Exhaust System	Steel Exhaust Pipe
Front Suspension	High-performance Dual Spring Shock Absorbers
Rear Suspension	Single Spring Shock Absorber
Brake System	Front & Rear Disc Brakes
Maximum Load Capacity	120 kg
Fuel Tank Capacity	3 L
Wheels	8-inch Steel Wheels, Front & Rear
Packing dimensions	1470 × 840 × 680 mm

Specifications, ordered configuration, CBU / SKD packing and market documents must be confirmed with the quotation. Single-unit trials available. Main-component warranty: 12 months, wear items excluded; contract terms apply.

YOUTH

ATV125-06

125cc Entry-Level ATV

An entry-level ATV for specialist off-road dealers. Rider suitability must follow the model manual.



Reference configuration | Off-road applications

Engine	125cc Single-cylinder, 4-stroke, Air-cooled, Fully Automatic Transmission, Electric Start
Drive System	Chain Drive
Ignition System	CDI
Frame	Heavy-duty Steel Frame
Handlebar	Steel Handlebar with Hand Guards
Exhaust System	Steel Exhaust Pipe
Front Suspension	High-performance Dual Spring Shock Absorbers
Rear Suspension	Single Spring Shock Absorber
Brake System	Front & Rear Disc Brakes
Maximum Load Capacity	120 kg
Fuel Tank Capacity	3 L
Wheels	8-inch Steel Wheels, Front & Rear
Packing dimensions	1470 × 840 × 680 mm

Specifications, ordered configuration, CBU / SKD packing and market documents must be confirmed with the quotation. Single-unit trials available. Main-component warranty: 12 months, wear items excluded; contract terms apply.

UTILITY

ATV300-21

300cc Utility ATV

A utility-focused ATV for importers building a practical off-road range.



Reference configuration | Off-road applications

Engine	Water-cooled, electric start
Drive system	Chain drive
Brakes	Front & rear disc brakes
Tires	Front 25×8-12 / Rear 25×10-12
Dimensions	1940 × 1090 × 915 mm
Net / gross weight	230 / 265 kg
Maximum load	260 kg
Packing dimensions	1950 × 1100 × 800 mm

Specifications, ordered configuration, CBU / SKD packing and market documents must be confirmed with the quotation. Single-unit trials available. Main-component warranty: 12 months, wear items excluded; contract terms apply.

UTILITY

ATV350-01

350cc 4WD Utility ATV

A utility-focused ATV for importers building a practical off-road range.



Reference configuration | Off-road applications

Engine	350cc, four-stroke, water-cooled
Transmission	CVT
Drive system	4WD, front & rear half-shaft drive
Brakes	Front & rear hydraulic disc brakes
Dimensions	1850 × 1300 × 1200 mm
Packing dimensions	2200 × 1080 × 880 mm

Specifications, ordered configuration, CBU / SKD packing and market documents must be confirmed with the quotation. Single-unit trials available. Main-component warranty: 12 months, wear items excluded; contract terms apply.

UTILITY

ATV350-21

350cc 4WD Utility ATV

A utility-focused ATV for importers building a practical off-road range.



Reference configuration | Off-road applications

Engine	350cc, Single-Cylinder, Four-Stroke, Water-Cooled Engine
Maximum Power	20 kW (27.2 HP) / 6000 rpm
Starting System	Electric Start
Transmission	Automatic Gear with H-N-L+R
Drive System	Shaft Drive, Selectable 4×2 / 4×4
Brake System	Front & Rear Hydraulic Disc Brakes
Suspension System	Adjustable Hydraulic Shock Absorbers
Tire Specification	Front 25×8-12 / Rear 25×10-12
Fuel Tank Capacity	9 L
Seat Height	900 mm
Wheel Track	970 mm
Ground Clearance	320 mm
Net Weight / Gross Weight	310 kg / 320 kg
Maximum Speed	75 km/h
Maximum Load Capacity	310 kg
Vehicle Dimensions	2010 × 1160 × 1210 mm
Packing dimensions	2000 × 1150 × 850 mm

Specifications, ordered configuration, CBU / SKD packing and market documents must be confirmed with the quotation. Single-unit trials available. Main-component warranty: 12 months, wear items excluded; contract terms apply.

UTILITY

ATV400-21

400cc EFI & EPS Utility ATV

A utility-focused ATV for importers building a practical off-road range.



Reference configuration | Off-road applications

Engine	400cc, Single-Cylinder, Four-Stroke, Water-Cooled Engine
Maximum Power	22 kW (29.8 HP) / 7000 rpm
Starting System	Electric Start with EFI & EPS (Electronic Power Steering)
Transmission	Automatic CVT (Forward / Neutral / Reverse)
Drive System	4WD Shaft Drive
Brake System	Front & Rear Disc Brakes
Suspension System	Adjustable Hydraulic Shock Absorbers
Tire Specification	Front 25×8-12 / Rear 25×10-12
Fuel Tank Capacity	9 L
Seat Height	900 mm
Wheelbase	1400 mm
Ground Clearance	300 mm
Net Weight / Gross Weight	325 kg / 345 kg
Maximum Speed	80 km/h
Maximum Load Capacity	240 kg
Vehicle Dimensions	2050 × 1160 × 1200 mm
Packing dimensions	2000 × 1150 × 850 mm

Specifications, ordered configuration, CBU / SKD packing and market documents must be confirmed with the quotation. Single-unit trials available. Main-component warranty: 12 months, wear items excluded; contract terms apply.

SPORT

ATV500-22

500-Class EFI & EPS ATV

A larger-engine ATV with shaft drive and hydraulic suspension for an off-road product range.

Reference configuration | Off-road applications



Engine	495cc, single-cylinder, four-stroke, water-cooled
Fuel system	EFI
Maximum power	28 kW / 7000 rpm
Maximum torque	43 N·m / 5800 rpm
Transmission	CVT, H / L / N / R
Drive system	4WD shaft drive
Steering	EPS
Suspension	Adjustable hydraulic shock absorbers
Brakes	Front & rear dual disc brakes
Tires	Front 26×9-14 / Rear 26×11-14
Fuel tank	10.5 L
Ground clearance	350 mm
Dimensions	2050 × 1160 × 1250 mm
Wheelbase	1390 mm
Net / gross weight	360 / 398 kg
Maximum load	240 kg
Packing dimensions	2280 × 1280 × 850 mm

Specifications, ordered configuration, CBU / SKD packing and market documents must be confirmed with the quotation. Single-unit trials available. Main-component warranty: 12 months, wear items excluded; contract terms apply.

SPORT

ATV500-23

500cc EFI & EPS ATV

A larger-engine ATV with shaft drive and hydraulic suspension for an off-road product range.



Reference configuration | Off-road applications

Engine	500cc, Single-Cylinder, Four-Stroke, Water-Cooled Engine
Maximum Power	28 kW (38 HP) / 7000 rpm
Starting System	Electric Start with EFI & EPS (Electronic Power Steering)
Transmission	Automatic CVT with D / N / R (Forward / Neutral / Reverse)
Drive System	Shaft Drive with Selectable 2WD / 4WD
Brake System	Front & Rear Hydraulic Disc Brakes
Suspension System	Hydraulic Shock Absorbers
Tire Specification	Front 26×9-14 / Rear 26×11-14
Fuel Tank Capacity	9 L
Seat Height	980 mm
Wheelbase	1390 mm
Ground Clearance	320 mm
Net Weight / Gross Weight	360 kg / 390 kg
Maximum Speed	75 km/h
Maximum Load Capacity	310 kg
Vehicle Dimensions	2050 × 1160 × 1250 mm
Packing dimensions	2280 × 1280 × 850 mm

Specifications, ordered configuration, CBU / SKD packing and market documents must be confirmed with the quotation. Single-unit trials available. Main-component warranty: 12 months, wear items excluded; contract terms apply.

UTV

UTV800-21

800cc V-Twin Utility UTV

Side-by-side seating and a cargo-oriented layout for work and fleet applications.



Reference configuration | Off-road applications

Engine	800cc V-twin, four-stroke, water-cooled
Fuel system	Bosch EFI
Maximum power	44 kW / 7000 rpm
Maximum torque	73 N·m / 5500 rpm
Transmission	L / H / N / R / P
Drive system	Selectable 4WD, shaft drive
Seating	2 seats, left-hand drive
Brakes	Four-wheel hydraulic disc brakes
Suspension	Front & rear independent double-wishbone
Fuel tank	27 L
Ground clearance	280 mm
Wheelbase	2580 mm
Dimensions	3500 × 1480 × 1870 mm
Net / gross weight	718.5 / 838 kg
Maximum vehicle load	300 kg
Cargo bed load limit	150 kg
Tires	Front 25×8-12 / Rear 25×10-12
Packing dimensions	2320 × 1470 × 1240 mm

Specifications, ordered configuration, CBU / SKD packing and market documents must be confirmed with the quotation. Single-unit trials available. Main-component warranty: 12 months, wear items excluded; contract terms apply.

ELECTRIC

UTV3000E21

72V 3000W Electric Utility UTV

An electric utility vehicle for buyers evaluating a battery-powered working fleet.



Reference configuration | Off-road applications

Motor	72V / 3000W
Battery	72V 80Ah; chemistry to be confirmed for the order
Transmission	Automatic F / N / R
Drive system	2WD shaft drive
Brakes	Front & rear hydraulic disc brakes, parking brake
Suspension	Front double A-arm; hydraulic shock absorbers
Tires	Front 23×7-10 / Rear 22×10-10
Ground clearance	260 mm
Wheelbase	1900 mm
Net / gross weight	400 / 430 kg
Maximum load	500 kg
Cargo bed dimensions	1000 × 1000 × 450 mm
Packing dimensions	2280 × 1290 × 950 mm

Specifications, ordered configuration, CBU / SKD packing and market documents must be confirmed with the quotation. Single-unit trials available. Main-component warranty: 12 months, wear items excluded; contract terms apply.